



Your Trust Expertise in Water
& Wastewater Treatment

eActive

Granular Activated Carbon

APPLICATION

eActive is a steam Activated Granular Carbon, that can be used in a large range of purification application:

Water purification: Drinking Water, Industrial water, Gas purification

eActive meets the requirements of J ISK 1474-1991 of Japanese Standard

RAW MATERIAL

Raw Material Coconut Shell

Activation Method Steam

SPECIFICATION

Apparent density	450 – 500 kg/m ³
Particle Size	8x30 mesh, 8x20 mesh 1.5mm
Packaging	25kg/bag
Original	Vietnam

TYPICAL ANALYSES

Analysis Method: J IS K – 1474 Japanese

Shape	Natural granular
Apparent density	450kg/m ³
Hydrotrope	1.5%
Moisture	Max 2.45 w/w %
Ash conten	0.01 w/w %
Intensity.	96%
Lodine No	650-970 mg/g
Benzene No	Min 23mg/g
pH value	alkaline 9 – 11
Hard index	min 95 w/ ww%

EAC VIETNAM CORPORATION

Unit 301, AGC Building - No.1, Lane 120 Truong Chinh Street, Dong Da District, Hanoi - Vietnam

Tel: +84 4 6285 6699 - Fax: +84 4 6285 3368 - Email: info@eacvn.com - Website: www.eacvn.com